




Class 8x19 & 8x36 MasterForm™ Compacted Strands



8xK26WS-IWRC
Warrington-Seale



8xK31WS-IWRC
Warrington-Seale



8xK36WS-IWRC
Warrington-Seale

Main Applications:

- Heavy duty winches
- Hoists, mostly when working in pairs (left lay & right lay).
- Applications requiring good resistance against drum crushing & fatigue.

Nominal Diameter	Approximate Mass	Minimum Breaking Force					
		IPS		EIPS		EEIP	
inch	lb./100ft.	tons	lb.	tons	lb.	tons	lb.
3/8	28.2	7.8	15500	8.6	17200	9.5	18900
7/16	38.3	10.5	21000	11.7	23400	12.7	25400
1/2	50.1	13.7	27400	15.2	30400	16.5	33000
9/16	63.4	17.3	34600	19.3	38500	20.8	41600
5/8	78.2	21.4	42700	23.8	47500	25.6	51100
3/4	113	30.7	61400	34.1	68200	36.7	73300
7/8	153	41.8	83500	46.4	92800	49.8	99600
1	200	54.6	109100	60.6	121100	64.9	129800
1 1/8	254	69.0	138000	76.7	153300	82.1	164100
1 1/4	313	85.2	170300	94.6	189200	101	202400
1 3/8	379	103	206000	114	228900	122	244800

The information in this brochure was prepared with utmost care but it is for reference only and is subject to change without notice



Wire Rope Works Messilot Ltd.
Doar Na Bet Shean 10804
ISRAEL
tel: ++972-4-6066-333
fax: ++972-4-6066-237
e-mail: messilot@messilot.org.il
110/I/9 - May 2013



© Wire Rope Works
Messilot Ltd.