


Class 19x7 Rotation Resistant Ropes



18x7-WSC

Main Applications:


- Tower cranes
- Hoists with single fall reeving (1:1)
- Hoists with multiple fall reeving but large length \ height

Nominal Diameter	Approximate Mass	Minimum Breaking Force			
		IPS		EIPS	
inch	lb./100ft.	tons	lb.	tons	lb.
1/4	11.1	2.51	5020	2.77	5540
5/16	17.4	3.90	7800	4.30	8600
3/8	25.0	5.59	11180	6.15	12300
7/16	35.0	7.58	15160	8.33	16660
1/2	45.0	9.85	19700	10.8	21600
9/16	58.0	12.4	24800	13.6	27200
5/8	71.0	15.3	30600	16.8	33600
3/4	102	21.8	43600	24.0	48000
7/8	139	29.5	59000	32.5	65000
1	182	38.3	76600	42.2	84400
1 1/8	230	48.2	96400	53.1	106200
1 1/4	284	59.2	118400	65.1	130200

The information in this brochure was prepared with utmost care but it is for reference only and is subject to change without notice



Wire Rope Works Messilot Ltd.
Doar Na Bet Shean 10804
ISRAEL
tel: ++972-4-6066-333
fax: ++972-4-6066-237
e-mail: messilot@messilot.org.il
110/I/12 - June 2009



© Wire Rope Works
Messilot Ltd.