




Class 8x19 & 8x36 For Wire Rope Hoists




8x19S-IWRC



8x19W-IWRC



8x25F-IWRC



8x36WS-IWRC

Main Applications:


- Winches
- Hoists, multiple fall reeving

Nominal Diameter mm	Approximate Mass kg/100m	Minimum Breaking Force					
		Grade 1770 N/mm ²		Grade 1960 N/mm ²		Grade 2160 N/mm ²	
		kN	kgF	kN	kgF	kN	kgF
7	19.9	30.9	3150	34.2	3490	37.7	3840
7.5	22.9	35.3	3600	39.1	3990	43.4	4430
8	26.0	40.3	4110	44.7	4560	49.2	5020
9	33.0	51.0	5200	56.5	5760	62.3	6350
10	40.7	63.0	6420	69.8	7120	76.9	7840
11	49.2	76.2	7770	84.4	8610	93.0	9480
12	58.6	90.7	9250	100	10200	111	11300
13	68.8	106	10800	118	12000	130	13300
14	79.8	124	12600	137	14000	151	15400
16	104	161	16400	179	18300	197	20100
18	132	204	20800	226	23000	249	25400
19	147	227	23100	252	25700	278	28300
20	163	252	25700	279	28500	308	31400
22	197	305	31100	338	34500	372	37900
24	234	363	37000	402	41000	443	45200
26	275	426	43400	472	48100	520	53000
28	319	494	50400	547	55800	603	61500
32	417	645	65800	715	72900	787	80300
36	527	817	83300	904	92200	997	101700

The information in this brochure was prepared with utmost care but it is for reference only and is subject to change without notice



Wire Rope Works Messilot Ltd.
Doar Na Bet Shean 10804
ISRAEL
tel: ++972-4-6066-333
fax: ++972-4-6066-237
e-mail: messilot@messilot.org.il
110/M/10 - June 2009



© Wire Rope Works
Messilot Ltd.