


35(W)x7 Rotation Resistant Ropes



35(W)x7 Rotex-Plus

Main Applications:


- Tower cranes
- Hoists with single fall reeving (1:1)
- Hoists with multiple fall reeving but large length \ height

Nominal Diameter mm	Approximate Mass kg/100m	Minimum Breaking Force			
		Grade 1960 N/mm ²		Grade 2160 N/mm ²	
		kN	kgF	kN	kgF
9	36.2	61.3	6260	66.8	6810
10	45.4	75.5	7700	82.2	8380
11	54.6	91.3	9310	99.4	10100
12	64.0	109	11100	119	12100
13	76.2	128	13100	139	14200
14	88.6	148	15100	161	16400
15	103	170	17300	185	18900
16	116	193	19700	210	21400
18	145	244	24900	266	27100
19	162	272	27700	296	30200
20	180	302	30800	329	33500
22	222	365	37200	397	40500

The information in this brochure was prepared with utmost care but it is for reference only and is subject to change without notice



Wire Rope Works Messilot Ltd.
Doar Na Bet Shean 10804
ISRAEL
tel: ++972-4-6066-333
fax: ++972-4-6066-237
e-mail: messilot@messilot.org.il
110/M/14 - June 2009



© Wire Rope Works
Messilot Ltd.