




# Class 6x19 & 6x36 MasterForm™ Compacted Strands




6xK19S-IWRC  
Seale



6xK26WS-IWRC  
Warrington-Seale



6xK31WS-IWRC  
Warrington-Seale



6xK36WS-IWRC  
Warrington-Seale

## Main Applications:


- Winches
- Hoists, mostly when working in pairs (left lay & right lay).
- Applications requiring good resistance against drum crushing & fatigue.

Nominal Diameter mm	Approximate Mass kg/100m	Minimum Breaking Force					
		Grade 1770 N/mm <sup>2</sup>		Grade 1960 N/mm <sup>2</sup>		Grade 2160 N/mm <sup>2</sup>	
		kN	kgF	kN	kgF	kN	kgF
10	46.9	75.9	7740	84.3	8600	91.5	9330
11	55.9	88.3	9000	98.1	10000	113	11500
12	66.5	103	10500	114	11600	127	13000
13	78.1	131	13360	145	14800	157	16000
14	90.6	151	15400	168	17100	183	18700
16	118	194	19800	216	22000	228	23300
18	150	244	24900	271	27600	298	30400
19	167	272	27700	302	30800	323	32900
20	185	300	30600	333	34000	355	36200
22	224	358	36500	398	40600	423	43100
24	266	438	44700	487	49700	518	52800
26	312	518	52800	576	58700	610	62200
28	362	590	60200	655	66800	700	71400
30	416	680	69300	755	77000	806	82200
32	473	760	77500	844	86000	914	93200

The information in this brochure was prepared with utmost care but it is for reference only and is subject to change without notice



Wire Rope Works Messilot Ltd.  
Doar Na Bet Shean 10804  
ISRAEL  
tel: ++972-4-6066-333  
fax: ++972-4-6066-237  
e-mail: messilot@messilot.org.il  
110/M/9 - June 2009



© Wire Rope Works  
Messilot Ltd.