




Table 9: Class 9x19 Parallel Closed Core




9x17S-PWRC
Seale



9x19S-PWRC
Seale



9x21F-PWRC
Filler



9x25F-PWRC
Filler

Nominal Diameter inch	Approximate Mass		Minimum Breaking Force Grade 1570/1770 N/mm ²	
	lbs / 100 ft		lbs	
5/16	18.3		9150	
3/8	26.1		13400	
7/16	35.4		18500	
1/2	46.1		24300	
9/16	58.2		30900	
5/8	71.8		38200	
3/4	86.7		46300	

Nominal Diameter mm	Approximate Mass		Minimum Breaking Force Grade 1570/1770 N/mm ²	
	Kg/100m	lbs / 100 ft *	kN	lbs *
8	26.0	17.5	42.1	9450
9	35.0	23.5	54.4	12200
10	43.0	28.9	66.0	14800
11	52.5	35.3	80.5	18100
12	61.0	41.0	95.1	21400
13	71.8	48.2	112	25200
14	83.1	55.8	130	29200
16	111	74.6	174	39100
19	151	101	245	55100

* Metric units take precedence, imperial units shown only for convenience.



Wire Rope Works Messilot Ltd.
Doar Na Bet Shean 10804
ISRAEL
tel: ++972-4-6066-333
fax: ++972-4-6066-237
e-mail: messilot@messilot.org.il
June 2011



© Wire Rope Works
Messilot Ltd.