




# Class 6x19




6x19S-FC  
Seale




6x19F-SFC  
Filler




6x26WS-SFC  
Warrington-Seale



6x19S-IWRC  
Seale



6x25F-IWRC  
Filler



6x26WS-IWRC  
Warrington-Seale

## Main Applications:


- Winches
- Hoists
- Static ropes; guys, stays, etc.
- Application in which service life depends mostly on wear

Nominal Diameter inch	Approximate Mass		Minimum Breaking Force					
	Fiber Core lb./100ft.	Steel Core	Fiber Core IPS		Steel Core IPS		Steel Core EIPS	
			tons	lb.	tons	lb.	tons	lb.
1/4	10.5	11.6	2.74	5480	2.94	5880	3.40	6800
5/16	16.4	18.0	4.26	8520	4.58	9160	5.27	10540
3/8	23.6	26.0	6.10	12200	6.56	13120	7.55	15100
7/16	32.0	35.0	8.27	16540	8.89	17780	10.2	20400
1/2	42.0	46.0	10.7	21400	11.5	23000	13.3	26600
9/16	53.0	59.0	13.5	27000	14.5	29000	16.8	33600
5/8	66.0	72.0	16.7	33400	17.7	35400	20.6	41200
3/4	95.0	104	23.8	47600	25.6	51200	29.4	58800
7/8	129	142	32.2	64400	34.6	69200	39.8	79600
1	168	185	41.8	83600	44.9	89800	51.7	103400
1 1/8	213	234	52.6	105200	56.5	113000	65.0	130000
1 1/4	263	289	64.6	129200	69.4	138800	79.9	159800
1 3/8	318	350	77.7	155400	83.5	167000	96.0	192000
1 1/2	378	416	92.0	184000	98.9	197800	114.0	228000

The information in this brochure was prepared with utmost care but it is for reference only and is subject to change without notice



Wire Rope Works Messilot Ltd.  
Doar Na Bet Shean 10804  
ISRAEL  
tel: ++972-4-6066-333  
fax: ++972-4-6066-237  
e-mail: [messilot@messilot.org.il](mailto:messilot@messilot.org.il)  
110/I/7 - June 2009



© Wire Rope Works  
Messilot Ltd.