




# Class 6x19 & 6x36 MasterForm™ Compacted Strands




6xK19S-IWRC  
Seale



6xK26WS-IWRC  
Warrington-Seale



6xK31WS-IWRC  
Warrington-Seale



6xK36WS-IWRC  
Warrington-Seale

## Main Applications:


- Winches
- Hoists, mostly when working in pairs (left lay & right lay).
- Applications requiring good resistance against drum crushing & fatigue.

Nominal Diameter	Approximate Mass	Minimum Breaking Force			
		EIPS		EEIP	
inch	lb./100ft.	tons	lbs.	tons	lbs.
3/8	28.2	8.30	16600	9.13	18300
7/16	38.3	11.2	22400	12.3	24600
1/2	50.1	14.6	29200	16.1	32200
9/16	63.4	18.5	37000	20.4	40800
5/8	78.2	22.7	45400	25.0	50000
3/4	113	32.4	64800	35.6	71200
7/8	153	43.8	87600	48.2	96400
1	200	56.9	113800	62.6	125200
1 1/8	254	71.5	143000	78.7	157400
1 1/4	313	87.9	175800	96.7	193400

The information in this brochure was prepared with utmost care but it is for reference only and is subject to change without notice



Wire Rope Works Messilot Ltd.  
Doar Na Bet Shean 10804  
ISRAEL  
tel: ++972-4-6066-333  
fax: ++972-4-6066-237  
e-mail: messilot@messilot.org.il  
110/I/9 - Jan 2011



© Wire Rope Works  
Messilot Ltd.